

FEATURES

Nippon Paint Pylac Pro is a nitrocellulose paint suitable for decorating wood and metal surfaces e.g. furniture and fence.

- Good Hiding
- Weather resistant
- Not ease to sagging.
- 2 caps are available for different uses.
- Can be used on various surfaces e.g. metal plastic and wood.

PRODUCT INFORMATION

Paint type	Nitrocellulose spray paint
Product type	Interior and Exterior
Film appearance	Gloss / Matt / Metallic
Color	Standard colours as per colour cards
Grade	Premium
Recommended substrate	Cement, Wood, Plastic and Steel
Pack size	400 cc

TECHNICAL INFORMATION

Coverage	2-3	m ² per can
	(Dependent on application condition and surface condition)	
No. of coat	1-2	coats
	(Dependent on the required area that is the paint will cover)	
Dry film thickness	30-40	microns
Touch dry (25-30°C)	5-10	mins

REFERENCE STANDARD

-

APPLICACION

Applicator	-
Diluted by	-
Dilution (%)	-

SURFACE PREPARATION

Metal	Surface must be dry and free from dirt, grease and other contaminants. Ferrous substrate should be sanded or wire-brushed to remove mill scales and rust. Clean off dust and dry.
Wood	Wood must be dry and free from dirt, grease and other contaminants. Smoothen surface with sand paper, then clean off and dry.
Old surface of cement	Remove all loose, defective paint or powdery residues, loose chalk, dust, fungus, algae and foreign matter. (avoid wire brush) Repair cracks, uneven surfaces with Nippon Paint Vinilex Wall Putty. Treat any areas affected by fungus growth by scrubbing and allowing the surface to dry

New surface of cement

completely before painting then apply with Nippon Paint Vinilex Bio Wash 1 coat and leave it until dry.

Ensure that the surface is clean and dry it must be free from dirt, greases and other foreign matters. Allow all surfaces to dry completely prior to painting. (At least 28 days) Avoid painting when the moisture content and alkalinity of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 14% measured by protimeter, below 6% by Kett model HI-520 and alkalinity of the walls to be below pH 8.) Repair cracks, uneven surfaces with Nippon Paint Vinilex Wall Putty.

Other surfaces

Ensure that the surface is clean and dry it must be free from dirt, greases and other foreign matters.

PAINT SYSTEM

Primer for metal surface

Nippon Paint Pylac Pro P-32 1 coat for preventing rust and then follow by Nippon Pylac Pro P-33 1 coat for the primer coat.

Primer for cement surface

Nippon Paint Excel Primer 1 coat or Nippon Pylac Pro P-33 1 coat

Primer for wood surface

Apply Nippon Paint Bodelac Undercoat White for preventing fungi and prime scrap spot areas of wood.

Top coat

Nippon Paint Pylac Pro 1-2 coats

Note: In case of vivid and intense color shade, a lighter shade is recommended to apply in the first coat for a good hiding result.

HANDLING AND STORAGE

Storage condition

The product must be stored in a dry, well-ventilated space and keep the container tightly closed. When transporting paint, the product should separately from others. Not recommended to place the product outdoor or exposed to the sun directly and must separately be stored between enamel paint and thinner, which is a flammable substance.

Precipitation

Place the product for a long time may lead the pigment to precipitate at the bottom of the container and can deteriorate over time when not stir product to a homogeneous by using suitable tools, such as an electric drill, air drill, or a stirrer. Therefore, should stir the product to the homogeneous phase before use. If not, the product will cause paint problems e.g. low hiding power or non-equal color shade.

Shelf life at 25-30 °C

5 years

SAFETY PRECAUTIONS

Precautionary notices are displayed on the container. Use product under well-ventilated area. Avoiding skin contact or inhale product. In case of contact with the eye, rinse with plenty of water immediately and seek medical advice. Remove splashes from the skin by using soap or water. For others information in terms of health and safety hazards for use of this product, please observe the Safety Data Sheet.

DISCLAIMER

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself.

We reserve the right to alter the given without prior notice.

NOTE

The data are average values for reference only. However, the actual value depends on environmental conditions.