

FEATURES

Nippon Paint Pylac 1000 is a nitrocellulose paint suitable for decorating motorcycle and automotive surfaces. It's can be spray on spares part or body of automotive.

- Provides a good metallic colour shade.
- Protect metal surface from corrosion.
- Can be used on various surfaces e.g. metal plastic and wood.
- Suitable for spares part and body of automotive.
- High solid and fast dry

PRODUCT INFORMATION

Paint type	Nitrocellulose spray paint
Product type	Interior and Exterior
Film appearance	Gloss / Matt (Only 229 colour shade for gloss and matt / 130 for rust preventive)
Color	Standard colours as per colour cards
Grade	Premium
Recommended substrate	Spares part or body of automotive.
Pack size	400 cc

TECHNICAL INFORMATION

Coverage	2-3	m ² per can
	(Dependent on application condition and surface condition)	
No. of coat	1-2	coats
	(Dependent on the required area that is the paint will cover)	
Dry film thickness	30-40	microns
Touch dry (25-30°C)	5-10	mins
Hard dry (25-30°C)	40-50	mins

REFERENCE STANDARD

-

APPLICATOR

Applicator

-

Diluted by	-
Dilution (%)	-

SURFACE PREPARATION

Metal	Surface must be dry and free from dirt, grease and other contaminants. Ferrous substrate should be sanded or wire-brushed to remove mill scales and rust. Clean off dust and dry.
Wood	Wood must be dry and free from dirt, grease and other contaminants. Smoothen surface with sand paper, then clean off and dry.
Other surfaces	Ensure that the surface is clean and dry it must be free from dirt, greases and other foreign matters.

PAINT SYSTEM

Primer for metal surface	Nippon Paint Pylac 1000 #130 1 coat for preventing rust and then follow by Nippon Pylac 1000 1 coat for the primer coat.
Primer for wood surface	Apply Nippon Paint Bodelac Undercoat White for preventing fungi and prime scrap spot areas of wood.
Top coat	Nippon Paint Pylac 1000 1-2 coats Note: In case of vivid and intense color shade, a lighter shade is recommended to apply in the first coat for a good hiding result.

HANDLING AND STORAGE

Storage condition	The product must be stored in a dry, well-ventilated space and keep the container tightly closed. When transporting paint, the product should separately from others. Not recommended to place the product outdoor or exposed to the sun directly and must separately be stored between enamel paint and thinner, which is a flammable substance.
Precipitation	Place the product for a long time may lead the pigment to precipitate at the bottom of the container and can deteriorate over time when not stir product to a homogeneous by using suitable tools, such as an electric drill, air drill, or a stirrer. Therefore, should stir the product to the homogeneous phase before use. If not, the product will cause paint problems e.g. low hiding power or non-equal color shade.
Shelf life at 25-30 °C	5 years

SAFETY PRECAUTIONS

Precautionary notices are displayed on the container. Use product under well-ventilated area. Avoiding skin contact or inhale product. In case of contact with the eye, rinse with plenty of water immediately and seek medical advice. Remove splashes from the skin by using soap or water. For others information in terms of health and safety hazards for use of this product, please observe the Safety Data Sheet.



DISCLAMER

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself.

We reserve the right to alter the given without prior notice.

NOTE

The data are average values for reference only. However, the actual value depends on environmental conditions.