

FEATURES

HealthCare is 100% Acrylic Emulsion paint with small molecule that help to prevent stain. It is effective against of bacteria and fungus caused pneumonia, diarrhea, allergy and other respiratory symptoms by Micro-Capsulated Shield technology.

- Anti-bacteria and anti-virus
- Resist the growth of coronavirus and influenza virus (H1N1) on paint film up to 99.9%*
- Excellent washability
- Resistance against fungus and algae
- Low odor and non-added lead or mercury
- Suitable for Green Building Standard including LEED v4, LEED v4.1, WELL and TREES.

*Tested by government laboratory institute. Coronavirus in the test is Porcine Epidemic Diarrhea Virus or PEDV which is similar

PRODUCT INFORMATION

| | |
|-----------------------|--|
| Paint type | 100% Acrylic Emulsion Paint |
| Product type | Interior |
| Film appearance | Matt |
| Colour | Various colors (see in colorcards & NIPPON PAINT fandeck) |
| Grade | Ultra Premium |
| Recommended substrate | Masonry, plastering, concrete, brick, fiber cement board, etc. |
| Pack size | 1 Gallon, 2.5 Gallon and 5 Gallon |

TECHNICAL INFORMATION

| | | |
|----------------------|--|------------------------------------|
| Theoretical coverage | 35-40 | m ² per gallon per coat |
| | (Actual coverage is dependent on substrate condition and application method) | |
| No. of coat | 2-3 | coats |
| Solid by volume | 34-38 | % |
| Solid by weight | 54-58 | % |
| VOC | < 5 | g/L |
| Wet film thickness | 100-110 | microns |
| Dry film thickness | 35-40 | microns |
| Touch dry (25-30°C) | 30 | minutes |
| Recoat dry (25-30°C) | 2 | hours |
| Full cure (25-30°C) | 7 | days |

REFERENCE STANDARD

| | | |
|---|---|------|
| TIS 2514-2564 (Solar heat reductive emulsion paint) | | n/a |
| TIS 2321-2564 (Weather-resistant emulsion paints) | ✓ | Pass |
| TIS 272-2564 (Emulsion paints for general purposes) | ✓ | Pass |
| THAI GREEN LABEL TGL-4-R4-14 | ✓ | Pass |
| MiT (Made in Thailand) | ✓ | Pass |
| Carbon Footprint Label (CFP) | ✓ | Pass |
| SCAQMD Rule 1113 | ✓ | Pass |
| CARB SCM 2007 | ✓ | Pass |
| LEED v4 & v4.1 VOC | ✓ | Pass |
| LEED v4 & v4.1 Emissions | ✓ | Pass |

| | | |
|---------------------------|---|------|
| TREES | ✓ | Pass |
| Nippon Paint Green Choice | ✓ | Pass |

APPLICATION

| | |
|--------------------|--|
| Application Method | Brush, Roller or Spray |
| Diluted by | Clean water |
| Dilution (%) | Dilute the paint with 5% by volume and mix thoroughly. |

SURFACE PREPARATION

| | |
|-------------|--|
| Old Surface | <p>Remove all loose, defective paint or powdery residues, loose chalk, dust, fungus, algae and foreign matter. (avoid wire brush)</p> <p>Repair cracks, uneven surfaces with Nippon Paint Vinilex Wall Putty or Nippon Paint Acrylic Sealant. Treat any areas affected by fungus growth by scrubbing and allowing the surface to dry completely before painting then apply with Nippon Paint Vinilex Bio Wash 1 coat and leave it until dry.</p> |
| New Surface | <p>Ensure that the surface is clean and dry it must be free from dirt, greases and other foreign matters. Allow all surfaces to dry completely prior to painting. (At least 28 days)</p> <p>Avoid painting when the moisture content and alkalinity of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 14% measured by protimeter, below 6% by Kett model HI-520 and alkalinity of the walls to be below pH 8.)</p> <p>Repair cracks and uneven surfaces with high-quality materials or decorate the surface appropriately before applying the paint.</p> |

PAINT SYSTEM

| | |
|------------------------------|---|
| Old Wall / Skim Coat Primer | Nippon Excel Primer (solvent based) 1 coat or Nippon Paint Aqua Sealer (water based) 1 coat |
| New Wall Primer | Nippon Paint 5200 Wall Sealer or Nippon Paint 5100 Wall Sealer 1 coat. |
| Hairline Cracked Wall Primer | Nippon Paint Flexiseal 1 coat. |
| Top Coat | Nippon Paint HealthCare 2-3 coats. |

**For deep tone, recommend applying the first coat with a lighter tone for good hiding performance.

HANDLING AND STORAGE

| | |
|-------------------|---|
| Storage condition | <p>The product must be stored in a dry, well-ventilated space and keep the container tightly closed. When transporting paint, the product should separately from others. Not recommended to place the product outdoor or exposed to the sun directly and must separately be stored between enamel paint and thinner, which is a flammable substance.</p> |
| Precipitation | <p>Place the product for a long time may lead the pigment to precipitate at the bottom of the container and can deteriorate over time when not stir product to a homogeneous by using suitable tools, such as an electric drill, air drill, or a stirrer. Therefore, should stir the product to the homogeneous phase before use. If not, the product will cause paint problems e.g. low hiding power or non-equal color shade.</p> |
| Shelf life | 5 years at 30-35 °C |

SAFETY PRECAUTIONS

Precautionary notices are displayed on the container. Use product under well-ventilated area. During use, the product must keep away from the source of ignition and no smoking. Avoiding skin contact or inhale product. In case of contact with the eye, rinse with plenty of water immediately and seek medical advice. Remove splashes from the skin by using soap or water. For others information in terms of health and safety hazards for use of this product, please observe the Safety Data Sheet.

DISCLAIMER

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself.

We reserve the right to alter the given without prior notice.

NOTE

The data are average values for reference only. However, the actual value depends on environmental conditions.