

FEATURES

Nippon Paint Gold Paint Lacquer is a fast-drying gold lacquer made from thermoplastic acrylic resin and nitrocellulose. It provides a brilliant gold metallic finish with long-lasting durability. Specially formulated for both exterior and interior walls, it offers exceptional weather resistance and excellent adhesion to various surfaces, including alkaline masonry substrates. The paint is washable and easy to clean.

- Durable against harsh weather
- Outstanding resistance to water and various chemicals
- Tough resistance against fungus and algae
- Tough resistance against alkali and efflorescence
- Excellent washability
- Superior adhesion to surfaces

PRODUCT INFORMATION

Paint type	Acrylic resin and Nitrocellulose
Product type	Exterior and Interior
Film appearance	Gloss
Colour	Various colours (see in the catalog)
Recommended substrate	Used as a substitute for traditional gold leaf application. Ideal for coating metal surfaces, Buddha statues, and similar objects.
Pack size	1 gallon

TECHNICAL INFORMATION

Theoretical coverage	11 - 13	m ² per gallon per coat
	(Actual coverage is dependent on substrate condition and application method)	
No. of coat	2	coats
Dry film thickness	25 - 30	microns
Touch dry (25-30°C)	5 - 10	mins
Recoat dry (25-30°C)	> 30	mins
Full cure (25-30°C)	7	days
	(Actual values may vary depending on environmental conditions. The above figures are average values provided for reference only.)	

APPLICATION

Application Method	Air Spray
Diluted by	Nippon Paint Gold Paint 1000 Thinner No. 10 or Nippon Paint Gold Paint 1000 Thinner No. 100
Dilution (%)	Dilute the paint with 70 - 100% by volume and mix thoroughly
Viscosity Spraying	10 - 13 seconds (NK Cup No. 2)
Air pressure	3.0 - 4.0 kg/cm ²
Air Spray Speed	100 - 120 cm/sec
	(The actual values may vary depending on environmental conditions. The figures provided are average values for reference only.)

SURFACE PREPARATION

Masonry surfaces	Ensure that the surface is clean and dry it must be free from dirt, greases and other foreign matters. Allow all surfaces to dry completely prior to painting. (At least 28 days Avoid painting when the moisture content and alkalinity of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 14% measured by protimeter, below 6% by Kett model HI-520 and alkalinity of the walls to be below pH 8.) Repair cracks, uneven surfaces with Nippon Paint Vinilex Wall Putty.
Metal, Stainless, Galvanized and copper etc.	Surface must be dry and free from dirt, grease and other contaminants. Ferrous substrate should be sanded or wire-brushed to remove mill scales and rust. Clean off dust and dry.

PAINT SYSTEM

Primer for masonry / metal	Nippon Paint Gold Paint Lacquer Undercoat 1 coat
Primer for glossy metal	Hi-Pon 30-06 (T) 1 coat or Hi-Pon 20-04 STE 80 1 coat, followed by 1 coat of Nippon Paint Gold Paint Lacquer Undercoat.
Topcoat	Nippon Paint Gold Paint Lacquer 2 coats

HANDLING AND STORAGE

Storage condition	The product must be stored in a dry, well-ventilated space and keep the container tightly closed. When transporting paint, the product should separately from others. Not recommended to place the product outdoor or exposed to the sun directly and must separately be stored between enamel paint and thinner, which is a flammable substance.
Precipitation	Place the product for a long time may lead the pigment to precipitate at the bottom of the container and can deteriorate over time when not stir product to a homogeneous by using suitable tools, such as an electric drill, air drill, or a stirrer. Therefore, should stir the product to the homogeneous phase before use. If not, the product will cause paint problems e.g. low hiding power or non-equal color shade.
Shelf life	2 years at 30 - 35 °C

SAFETY PRECAUTIONS

Precautionary notices are displayed on the container. Use product under well-ventilated area. During use, the product must keep away from the source of ignition and no smoking. Avoiding skin contact or inhale product. In case of contact with the eye, rinse with plenty of water immediately and seek medical advice. Remove splashes from the skin by using soap or water. For others information in terms of health and safety hazards for use of this product, please observe the Safety Data Sheet.

DISCLAIMER

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself. We reserve the right to alter the given without prior notice.

NOTE

The data are average values for reference only. However, the actual value depends on environmental conditions.