

FEATURES

Premium acrylic emulsion which is suitable for interior & exterior use for wooden wall and floor. Provides low odour and good film appearance.

- Weathering Resistance
- Fungus Resistance
- Lead & Mercury free
- Low VOC & Low Odour

PRODUCT INFORMATION

Paint type	Acrylic emulsion
Product type	Exterior & Interior
Film appearance	Sheen
Color	Various colors (see in color cards)
Grade	Premium
Recommended substrate	Wood substrate i.e. furniture, fiber cement and smart wood.
Pack size	1 Litre, 5 Litres

TECHNICAL INFORMATION

Theoretical coverage	10-12	m ² per Litre per coat (Dependent on application condition and surface condition)
No. of coat	2	coats
Solid by weight	38±2	%
VOC	n/a	
Wet film thickness	65-75	microns
Dry film thickness	30-40	microns
Touch dry (25-30°C)	15-20	mins
Recoat dry (25-30°C)	2-3	hrs.
Full cure (25-30°C)	7	days

REFERENCE STANDARD

-

APPLICATION

Applicator	Brush, Roller
Diluted by	Water
Dilution (%)	Dilute the paint with not more than 5% of water. Preferable not dilute for best performance.

SURFACE PREPARATION

Wood	Wood must be dry and free from dirt, grease and other contaminants. Smoothen surface with sand paper, then clean off and dry.
------	---

PAINT SYSTEM

Primer for wood surface	Nippon Paint Bodelac Undercoat White 1-2 coats
Top coat	Nippon Paint Timbershade 2 coats
	Note: In case of vivid and intense color shade, a lighter shade is recommended to apply in the first coat for a good hiding result.

HANDLING AND STORAGE

Storage condition	The product must be stored in a dry, well-ventilated space and keep the container tightly closed. When transporting paint, the product should separately from others. Not recommended to place the product outdoor or exposed to the sun directly and must separately be stored between enamel paint and thinner, which is a flammable substance.
Precipitation	Place the product for a long time may lead the pigment to precipitate at the bottom of the container and can deteriorate over time when not stir product to a homogeneous by using suitable tools, such as an electric drill, air drill, or a stirrer. Therefore, should stir the product to the homogeneous phase before use. If not, the product will cause paint problems e.g. low hiding power or non-equal color shade.
Shelf life	3 years at 30-35 °C

SAFETY PRECAUTIONS

Precautionary notices are displayed on the container. Use product under well-ventilated area. Avoiding skin contact or inhale product. In case of contact with the eye, rinse with plenty of water immediately and seek medical advice. Remove splashes from the skin by using soap or water. For others information in terms of health and safety hazards for use of this product, please observe the Safety Data Sheet.

DISCLAIMER

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself.

We reserve the right to alter the given without prior notice.

NOTE

The data are average values for reference only. However, the actual value depends on environmental conditions.