



FEATURES

JUNIOR 99 SPRAY is a acrylic paint that provides a good appearance, durable and also fast dry. It's can be uses both interior and exterior. Suitable for decorating and D.I.Y work

- · Easy to apply.
- · Good hiding
- Provides a good appearance and durable.
- Can be used on various surfaces e.g. metal plastic and wood.
- A distinctive variety of color shades.
- Economy

PRODUCT INFORMATION

Paint type Acrylic spray paint

Product type Interior and Exterior

Gloss / Matt Film appearance

Standard colours as per colour cards Color

Grade Economy

Recommended substrate Metal, plastic and wood.

Pack size 400 cc

TECHNICAL INFORMATION

m² per can 1.0-1.7 Coverage

(Dependent on experiences of user and also the appearance, sizing condition of substrate and

surface condition)

No. of coat 2-3 coats

(Dependent on the required area that is the paint will cover)

Dry film thickness 30-40 microns

Touch dry (25-30°C) 5-10 mins

Hard dry (25-30°C) 40-50 mins

REFERENCE STANDARD

Page 1/3





- A I	וחו	. ~	ΛTI	ON
Δ	JUI		Δ II	

Should shake the can before use for 1-2 minutes until the sound of the crystal ball inside the can clattering steadily. During spraying on substrate, product should be shake as well. For distance of spraying should be 30 centimeters far from substrate. After use, the spray nozzle should be cleaned by turning the can upside down and blowing out a little air to prevent clogging.

SURFACE PREPARATION

Metal Surface must be dry and free from dirt, grease and other contaminants. Ferrous substrate should

be sanded or wire-brushed to remove mill scales and rust. Clean off dust and dry.

Wood word free from dirt, grease and other contaminants. Smoothen surface with

sand paper, then clean off and dry.

Other surfaces Ensure that the surface is clean and dry it must be free from dirt, greases and other foreign

matters.

PAINT SYSTEM

Primer for metal surface Junior 99 spray in the primer color shade as per catalog for 1 coat.

Primer for wood surface Junior 99 spray in the primer color shade as per catalog for 1 coat.

Top coat Junior 99 spray for 2-3 coats.

Note: In case of vivid and intense color shade, a lighter shade is recommended to apply in the

first coat for a good hiding result.

HANDLING AND STORAGE

Storage condition The product must be stored in a dry, well-ventilated space and keep the container tightly closed.

When transporting paint, the product should separately from others. Not recommended to place the product outdoor or exposed to the sun directly and must separately be stored between the

heating resource and spark.

Precipitation Place the product for a long time may lead the pigment to precipitate at the bottom of the

container and can deteriorate over time when not shake to a homogeneous. Therefore, should shake the product to the homogeneous phase before use. If not, the product will cause paint

problems e.g. low hiding power or non-equal color shade.

Shelf life at 30-35 °C 2 years

Page 2/3



JUNIOR 99 SPRAY

SAFETY PRECAUTIONS

Precautionary notices are displayed on the container. Use product under well-ventilated area. Avoiding skin contact or inhale product. In case of contact with the eye, rinse with plenty of water immediately and seek medical advice. Remove splashes from the skin by using soap or water. For others information in terms of health and safety hazards for use of this product, please observe the Safety Data Sheet.

DISCLAMER

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself.

We reserve the right to alter the given without prior notice.

NOTE

The data are average values for reference only. However, the actual value depends on environmental conditions.

Page 3/3