

FEATURES

This multipurpose white water-based primer, with a 40% moisture resistance, is suitable for fresh plaster and new concrete. It features HYDRO BARRIER Technology to prevent alkali and salt migration, preventing color fading, and is suitable for both interior and exterior use.

- Excellent surface coverage
- Enhances adhesion between substrate and paint film
- Prevents alkali and salt stains
- Protects against mold and algae growth
- Water-based formula with low odor, safe for users and residents

PRODUCT INFORMATION

Paint type	100% Acrylic Emulsion Paint
Product type	Exterior and Interior
Film appearance	Matt
Colour	White
Grade	Premium
Recommended substrate	High-Moisture-Resistant Multipurpose Primer for fresh and new wall, suitable for both interior and exterior use. Ideal for Masonry, plastering, concrete, brick, fibre cement board, etc.
Pack size	1 Gallon and 5 Gallon

TECHNICAL INFORMATION

Theoretical coverage	35 - 40	m ² per gallon per coat
	(Actual coverage is dependent on substrate condition and application method)	
No. of coat	1	coat
Solid by volume	31 - 35	%
Solid by weight	46 - 50	%
VOC	-	g/L
Wet film thickness	100 - 110	microns
Dry film thickness	35 - 40	microns
Touch dry (25-30°C)	30	minutes (depending on temperture and environment)
Recoat dry (25-30°C)	2	hours (depending on temperture and environment)
Full cure (25-30°C)	7	days (depending on temperture and environment)

REFERENCE STANDARD

TIS 1123 - 2555 (Plaster primer)	✓	Pass
----------------------------------	---	------

APPLICATION

Application Method	Brush, Roller or Spray
Diluted by	Clean water
Dilution (%)	Dilute the paint with 5% by volume and mix thoroughly.

SURFACE PREPARATION

New Surface	Ensure that the surface is clean and dry it must be free from dirt, greases and other foreign matters. Allow all surfaces to dry completely prior to painting. (At least 28 days)
-------------	--

Avoid painting when the moisture content and alkalinity of the walls are still high. (Recommended painting specification requires the moisture content of the walls to be below 14% measured by protimeter, below 6% by Kett model HI-520 and alkalinity of the walls to be below pH 8.)

Repair cracks and uneven surfaces with high-quality materials or decorate the surface appropriately before applying the paint.

PAINT SYSTEM

New Wall Primer	Nippon Paint Quickcoat Primer 1 coat
Top Coat	For exterior; Nippon Paint Weatherbond 2 - 3 coats. For Interior; Nippon Paint AirCare 2 - 3 coats. **For deep tone, recommend applying the first coat with a lighter tone for good hiding performance.

HANDLING AND STORAGE

Storage condition	The product must be stored in a dry, well-ventilated space and keep the container tightly closed. When transporting paint, the product should separately from others. Not recommended to place the product outdoor or exposed to the sun directly and must separately be stored between enamel paint and thinner, which is a flammable substance.
Precipitation	Place the product for a long time may lead the pigment to precipitate at the bottom of the container and can deteriorate over time when not stir product to a homogeneous by using suitable tools, such as an electric drill, air drill, or a stirrer. Therefore, should stir the product to the homogeneous phase before use. If not, the product will cause paint problems e.g. low hiding power or non-equal color shade.
Shelf life	5 years at 30 - 35 °C

SAFETY PRECAUTIONS

Precautionary notices are displayed on the container. Use product under well-ventilated area. During use, the product must keep away from the source of ignition and no smoking. Avoiding skin contact or inhale product. In case of contact with the eye, rinse with plenty of water immediately and seek medical advice. Remove splashes from the skin by using soap or water. For others information in terms of health and safety hazards for use of this product, please observe the Safety Data Sheet.

DISCLAIMER

The above information is given to the best of our knowledge based on laboratory tests and practical experience. However, since we cannot anticipate or control the many conditions under which our products may be used, we can only guarantee the quality of the product itself. We reserve the right to alter the given without prior notice.

NOTE

The data are average values for reference only. However, the actual value depends on environmental conditions.